

TECHNICAL SPECIFICATIONS RGP406 WILD

Type Tufted non filled synthetic grass carpet

Yarn Material PE monofilament Rectangle shape & PP monofilament curled

Yarn dTex 17.400 Dtex / 24 ply

Yarn Quality environmental friendly, UV stabilized

Primary Backing 100% PP with fibre-lock fleece, black, UV stabilized

Weight: approx. 160 g/m² +/- 10%

Secondary Backing Black latex compound with a base of SBR, with drainage holes

Weight: approx. 685 g/m2 +/- 10%

Tuft gauge 3/8'

 Pile Height
 approx. 30 mm
 +/- 10%

 Total Height
 approx. 32 mm
 +/- 10%

 Pile gross weight
 approx. 1.425 g/m2
 +/- 10%

 Total weight
 approx. 2.270 g/m2
 +/- 10%

 # Knots per m2
 approx. 11.025
 +/- 10%

Lightfastness Bluescale 1-8 > 7 (according DIN 54004)
Colourfastness Greyscale 1-5 > 4 (according DIN standard)

UV Stability 8 years in moderate sunny regions

6 years in sunny regions

Roll width 4 meters +/- 1%

Roll length Target length approx. 25m

Water permeability > 60 I / min / m2

Infill recommendation In case of intensive use:

Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped

Approx. 5-8 kg per m2 for stabilisation

Shrinkage can appear due to high temperatures. Make sure the carpet can relax

before cutting

Application intensive used Lawns, public places, parks, ...

TSS-RGP526-09/2018