

TECHNICAL SPECIFICATIONS RGP437 DE LUXE

| | | |
|----------------------------|--|---------|
| Type | Tufted non filled synthetic grass carpet | |
| Yarn Material | PE monofilament C-/Waffle/Rectangle shape & PP monofilament curled | |
| Yarn dTex | 13.100 Dtex / 17 ply | |
| Yarn Quality | environmental friendly, UV stabilized DIN 53387 | |
| Primary Backing | 100% PP with fibre-lock fleece, black, UV stabilized | |
| | Weight : approx.. 200 g/m ² | +/- 10% |
| Secondary Backing | Black latex compound with a base of SBR, with drainage holes | |
| | Weight: approx. 720 g/m ² | +/- 10% |
| Tuft gauge | 5/8' | |
| Pile Height | approx. 40 mm | +/- 10% |
| Total Height | approx. 42 mm | +/- 10% |
| Pile gross weight | approx. 1.450 g/m ² | +/- 10% |
| Total weight | approx. 2.370 g/m ² | +/- 10% |
| # Knots per m ² | approx. 11.340 | +/- 10% |
| Lightfastness | Bluescale 1-8 > 7 (according DIN 54004) | |
| Colourfastness | Greyscale 1-5 > 4 (according DIN standard) | |
| UV Stability | 8 years in moderate sunny regions | |
| | 6 years in sunny regions | |
| Roll width | 4 meters | +/- 1% |
| Roll length | Target length approx. 25m | |
| Water permeability | > 60 l / min / m ² | |
| Infill recommendation | In case of intensive use: Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped Approx. 5-8 kg per m ² for stabilisation | |
| Shrinkage | Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting | |
| Application | Lawns, public places, parks, ... | |