

TECHNICAL SPECIFICATIONS RGP437 DE LUXE

Type Tufted non filled synthetic grass carpet

Yarn Material PE monofilament C-/Waffle/Rectangle shape & PP monofilament curled

Yarn dTex 13.100 Dtex / 17 ply

Yarn Quality environmental friendly, UV stabilized DIN 53387
Primary Backing 100% PP with fibre-lock fleece, black, UV stabilized

Weight: approx.. 200 g/m² +/- 10%

Secondary Backing Black latex compound with a base of SBR, with drainage holes

Weight: approx. 720 g/m2 +/- 10%

Tuft gauge 5/8'

 Pile Height
 approx. 40 mm
 +/- 10%

 Total Height
 approx. 42 mm
 +/- 10%

 Pile gross weight
 approx. 1.450 g/m2
 +/- 10%

 Total weight
 approx. 2.370 g/m2
 +/- 10%

 # Knots per m2
 approx. 11.340
 +/- 10%

Lightfastness Bluescale 1-8 > 7 (according DIN 54004)
Colourfastness Greyscale 1-5 > 4 (according DIN standard)

UV Stability 8 years in moderate sunny regions

6 years in sunny regions

Roll width 4 meters +/- 1%

Roll length Target length approx. 25m

Water permeability > 60 I / min / m2

Infill recommendation In case of intensive use:

Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped

Approx. 5-8 kg per m2 for stabilisation

Shrinkage can appear due to high temperatures. Make sure the carpet can relax

before cutting

Application Lawns, public places, parks, ...

ISS-RGP526-09/2018