

TECHNICAL SPECIFICATIONS RGP526

Type Tufted non filled synthetic grass carpet

Yarn Material 65% PE monofilament straight & 35% PP monofilament curled

Fibre Shape Xtra Spine Technology

Yarn Quality environmental friendly, UV stabilized Primary Backing 100% PP woven with fibre-lock fleece

Weight: approx.. 170 g/m² +/- 10%

Secondary Backing Black latex compound with a base of SBR, with drainage holes

Weight: approx. 800 g/m2 +/- 10%

Tuft gauge 3/8'

 Pile Height
 approx. 30 mm
 +/- 10%

 Total Height
 approx. 32 mm
 +/- 10%

 Pile gross weight
 approx. 887 g/m2
 +/- 10%

 Total weight
 approx. 1.857 g/m2
 +/- 10%

 # Knots per m2
 approx. 18.900
 +/- 10%

Lightfastness Bluescale 1-8 > 7 (according DIN 54004)
Colourfastness Greyscale 1-5 > 4 (according DIN standard)

UV Stability 8 years in moderate sunny regions

6 years in sunny regions

Roll width 4 meters +/- 1%

Roll length Target length approx. 30 m

Water permeability > 60 I / min / m2

Infill recommendation In case of intensive use:

Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped

Approx. 8 kg per m2 for stabilisation

Shrinkage can appear due to high temperatures. Make sure the carpet can relax

before cutting

Application Lawns, playgrounds, public places, parks, ...

ISS-RGP526-09/2018