

TECHNICAL SPECIFICATIONS RGP533

Type Tufted non filled synthetic grass carpet

Yarn Material 65% PE monofilament straight & 35% PP monofilament curled

Fibre Shape W-Shape

Yarn Quality environmental friendly, UV stabilized

Primary Backing 100% PP woven

Weight: approx.. 135 g/m² +/- 10%

Secondary Backing Black latex compound with a base of SBR, with drainage holes

Weight: approx. 900 g/m2 +/- 10%

Tuft gauge 5/16"

 Pile Height
 approx. 40 mm
 +/- 10%

 Total Height
 approx. 42 mm
 +/- 10%

 Pile gross weight
 approx. 2.300 g/m2
 +/- 10%

 Total weight
 approx. 3.335 g/m2
 +/- 10%

 # Knots per m2
 approx. 15.225
 +/- 10%

Lightfastness Bluescale 1-8 > 7 (according DIN 54004)
Colourfastness Greyscale 1-5 > 4 (according DIN standard)
UV Stability 8 years in moderate sunny regions

bility 8 years in moderate sunny regions 6 years in sunny regions

Roll width 4 meters +/- 1%

Roll length Target length approx. 25 m

Water permeability > 60 I / min / m2

Infill recommendation In case of intensive use:

Silica sand, gradation 0,5 - 0,10 mm / Min. 80% round-shaped

Approx. 8 kg per m2 for stabilisation

Shrinkage can appear due to high temperatures. Make sure the carpet can relax

before cutting

Application Lawns, playgrounds, public places, parks, ...

-SS-RGP533-09/2018