

TECHNICAL SPECIFICATIONS RGP535 DL

Type Tufted non filled synthetic grass carpet

Yarn Material PE monofilament C-shape straight & PP monofilament curled

Yarn Dtex 15.300

Yarn Quality environmental friendly, UV stabilized

Primary Backing 100% PP + Fleece

Weight: approx. 185 g/m2 +/- 10%

Secondary Backing black latex compound with a base of SBR, with drainage holes

Weight: approx. 1.000 g/m2 +/- 10%

Tuft gauge 3/8'

 Pile Height
 approx. 45 mm
 +/- 10%

 Total Height
 approx. 47 mm
 +/- 10%

 Pile gross weight
 approx. 1.950 g/m2
 +/- 10%

 Total weight
 approx. 3.135 g/m2
 +/- 10%

 # Knots per m2
 approx. 12.100
 +/- 10%

Lightfastness DIN 53387

UV Stability 8 years in moderate sunny regions (DIN 53387)

6 years in sunny regions

Roll width 4 meters +/- 1%

Roll length Target length approx. 20-25 m

Water permeability > 60 I / min / m2

Infill recommendation In case of intensive use:

Silica sand, gradation 0,5 - 0,10 mm / Min. 80% round-shaped

Approx. 5 kg per m2 for stabilisation

Shrinkage Shrinkage can appear due to high temperatures. Make sure the carpet can relax

before cutting

Application Lawns, public places, parks, ...