

TECHNICAL SPECIFICATIONS RGP538

Type	Tufted non filled synthetic grass carpet	
Yarn Material	PE monofilament ReSoft & PP monofilament curled	
Yarn dTex	7.250 dTex / 14 ply	
Fibre Shape	Waffle-Shape	
Yarn Quality	environmental friendly, UV stabilized DIN 53387	
Primary Backing	100% PP with fibre-lock fleece, black, UV stabilized	
	Weight : approx.. 160 g/m ²	+/- 10%
Secondary Backing	Black latex compound with a base of SBR, with drainage holes	
	Weight: approx. 685 g/m ²	+/- 10%
Tuft gauge	3/8'	
Pile Height	approx. 35 mm	+/- 10%
Total Height	approx. 37 mm	+/- 10%
Pile gross weight	approx. 1.405 g/m ²	+/- 10%
Total weight	approx. 2.250 g/m ²	+/- 10%
# Knots per m ²	approx. 23.100	+/- 10%
Lightfastness	Bluescale 1-8 > 7 (according DIN 54004)	
Colourfastness	Greyscale 1-5 > 4 (according DIN standard)	
UV Stability	8 years in moderate sunny regions 6 years in sunny regions	
Roll width	4 meters	+/- 1%
Roll length	Target length approx. 25,20 m	
Water permeability	> 60 l / min / m ²	
Infill recommendation	In case of intensive use: Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped Approx. 5 kg per m ² for stabilisation	
Shrinkage	Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Application	Lawns, playgrounds, public places, parks, ...	