

## **TECHNICAL SPECIFICATIONS RGP573**

Type	Tufted cut pile, non fill synthetic yarn	
Yarn Material	100% Polyethylene & Polypropylene	
Yarn Dtex	24.000 / 32 ply	
Yarn Quality	100% European product, free of lead and cadmium	
Primary Backing	100% PP with fibre locked fleece, UV stabilised	
Secondary Backing	Weight: approx. 160 g/m2	+/- 10%
	Water pervious SBR Latex	
	Weight: approx. 800 g/m2	+/- 10%
Tuft gauge	5/8'	
Pile Height	approx. 50 mm	+/- 10%
Total Height	approx. 52 mm	+/- 10%
Pile gross weight	approx. 2.380 g/m2	+/- 10%
Total weight	approx. 3.340 g/m2	+/- 10%
# Knots per m2	approx. 8.190	+/- 10%
Lightfastness	Bluescale 1-8 > 7 (according DIN 54004)	
Colourfastness	Greyscale 1-5 > 4 (according DIN standard)	
UV Stability	8 years in moderate sunny regions	
	6 years in sunny regions	
Roll width	4 meters	+/- 1%
Roll length	Target length approx. 22 m	
Water permeability	> 30 l / min / m2	
Infill recommendation	In case of intensive use: Silica sand, gradation 0,5 – 0,10 mm / Min. 80% round-shaped Approx. 5 kg per m2 for stabilisation.	
Shrinkage	Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Application	Lawns, playgrounds, public places, parks, ...	