ResiGrass

TECHNICAL SPECIFICATIONS RT611

Type Yarn material Yarn type Yarn quality Primary backing Secondary backing	Tufted infill synthetic yarn 100% Polyethylene, fibrillated, straight pile curled KDK 7.300/1 ply Environmental friendly – UV resistance Black uv resistant woven PP + fiber locked fleece Weight: 146 g/m2 +/- 10% Black latex compound based on SBR with drainage Weight: 988 g/m2 +/- 10%	
Tuft gauge Pile Height Total Height Pile gross weight Total weight # Knots per m2 # Piles per m2	3/8" 10 mm 12 mm ca 1.150 g/m2 ca 2.284 g/m2 ca 63.000 126.00	+/- 10% +/- 10% +/- 10% +/- 10% +/- 10% +/- 10%
Roll width Roll length Colour Marking Lines	3,72 - 4 meters Max. 70m Green, clay red Lining possible in white / yellow / red or blue	+/- 1%
Infill recommendation Shrinkage	Requires 12 kg/m ² infill (ca 9 mm) 80% round, granular size 0.3 – 0.8 mm Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Applications	Tannia Daddla	

Applications

Tennis, Paddle



ResiGrass retains the right to modify each product with the objective to improve its quality according to the newest technology and as such shall not be legally liable for any and all deviations and/or non-compliance with these specifications.